



FEIN



CCG 18-125-10 PD AS

Cordless angle grinder, 5 [125] in[mm] dia.

Dust-resistant and powerful cordless angle grinder with dead man's switch for effective cutting, grinding and deburring. (bare tool)

Product number: 7 122 04 60 09 0

Details

- + Guarantees the highest service life with the next generation of brushless FEIN PowerDrive motors. The completely closed motor housing protects the motor against aggressive ceramic and mineral dusts.
- + Ideal for any application. Optimal speeds, matched to many grinding materials. Variable speed to match grinding wheel RPM requirements.
- + High-performance. 30% more efficient than comparable universal motors with 1,080 watts of input power.
- + Delivers the same power as an equivalent 1,080-watt corded angle grinder.
- + Maintenance-free motor with innovative cooling fins for optimal heat dissipation including temperature monitoring.
- + COOLPACK 2.0 technology ensures a 135% longer battery service life, enabling longer operation time.
- + State-of-the-art cell technology and intelligent battery management deliver 87% more power than conventional batteries.
- + CORE 18 V Li-ion battery with Highpower cells, charge indicator and electronic cell protection (ECP). ECP protects batteries against overloading, overheating and deep discharge.
- + Smooth, vibration-free operation with the independently mounted motor, isolated from the housing and enhanced by four additional dampers.
- + Maximum user safety with soft start, restart prevention, electronic overload protection and a brake system.
- + Low-fatigue working with its slim grip, compact design and low weight with good balance.
- + Dust-protected, separate motor electronics in the grip area.
- + Compatible with all CORE 18 V AMPShare batteries and chargers, for even more power and flexibility. Also suitable for 18 V Bosch Professional cordless tools.
- + Quick setup with the tool-free adjustable safety guard and fast-clamping nut for maximum efficiency.
- + Well lit work area thanks to the integrated LED lights.
- + Easily transported with our stackable L-BOXX system.

Price includes

- + 1 guard
- + 1 anti-vibration handle
- + 1 tool-free quick-action clamping nut
- + 1 wrench

Product feature

- + Brake
- + Soft-start
- + Jam monitoring
- + Electronic speed selection
- + POWERtronic tachometer electronics
- + Restart protection
- + Electronic overload protection
- + AutoStop dead man's switch

Application



Material removal

+

Deburring

++

Cutting

++

Brushing

+

Satin finishing

++

+ suitable

++ well suitable

Technical data

TECHNICAL DATA

No load speed

2,500 - 8,500 rpm

Grinding wheel Ø

5 [125] in[mm]

Elastic backing pad Ø

5 [125] in[mm]

Mounting thread

5/8-11 in

Sound pressure level LpA
Measurement uncertainty of
the measured value KpA

86 dB
3 dB

Sound power level LWA
Measurement uncertainty of
the measured value KWA

97 dB
3 dB

Peak sound value
LpCpeak
Measurement uncertainty of
the measured value KpCpeak

99 dB
3 dB

Vibration value 1 α_{hv} 3-
way
Measurement uncertainty of
the measured value K α

4,9 m/s²
1,5 m/s²

Vibration value 2 α_{hv} 3-
way
Measurement uncertainty of
the measured value K α

1,5 m/s²
1,5 m/s²

Application examples



FEIN

