

AGSZ 18-280 BL AS

Cordless die grinder

Dust-resistant and powerful compact cordless die grinder for effective cutting, sanding, deburring and milling work.

Product number: 7 123 04 61 09 0



Details

- + Guarantees the highest service life with the next generation of brushless FEIN PowerDrive motors. The completely closed motor housing protects the motor against aggressive ceramic and mineral dusts.
- + Ideal for any application. Optimal speeds, matched to many grinding materials. Variable speed to match grinding wheel RPM requirements.
- + High-performance. 30% higher degree of efficiency than comparable universal motors with 1,100 watts of input power.
- + COOLPACK 2.0 technology ensures a 135% longer battery service life, enabling longer operation time.
- + State-of-the-art cell technology and intelligent battery management deliver 87% more power than conventional batteries.
- + Smooth, vibration-free operation with the independently mounted motor, isolated from the housing and enhanced by four additional dampers.
- + Extensive user protection through soft start, restart protection and electronic overload protection.
- + Innovative collets with wrap around collar for workpiece protection and to prevent the wrench slipping when changing tools.
- + Low-fatigue working with its slim grip, compact design and low weight with good balance.
- + Dust-protected, separate motor electronics in the grip area.
- + Compatible with all CORE 18 V AMPShare batteries and chargers, for even more power and flexibility. Also suitable for 18 V Bosch Professional cordless tools.
- + Well lit work area thanks to the integrated LED lights.
- + Perfectly equipped for any job with our L-BOXX system.

Price includes

- + 1 collet Ø 1/4 in [6 mm]
- + Spanner size 3
- + Spanner SW17
- + 1 plastic carrying case (L-BOXX 238)

Application

Cutting





Material removal

++

Grinding

++

Deburring

+

Brushing

+

+ suitable

++ well suitable

Technical data

TECHNICAL DATA

No load speed

9,000 - 28,000 rpm

Grinding wheel for max.
Ø

2 [50] in[mm]

Collet for max. Ø

1/4 [8] in[mm]

Milling machine max. dia.

1/2 [12] in[mm]

Sound pressure level LpA
Measurement uncertainty of
the measured value KpA

86,4 dB
3 dB

Sound power level LWA
Measurement uncertainty of
the measured value KWA

94,4 dB
3 dB

Peak sound value
LpCpeak
Measurement uncertainty of
the measured value KpCpeak

101,9 dB
3 dB

Vibration value 1 α_{hv} 3-
way
Measurement uncertainty of
the measured value K α

$\alpha_{h,SG}$ (Ø 50mm) 9,0
m/s²
1,5 m/s²

Vibration value 2 α_{hv} 3-
way
Measurement uncertainty of
the measured value K α

$\alpha_{h,SG}$ (Ø 25mm) 4,7
m/s²
1,5 m/s²

Application examples



FEIN



Powered by



BOSCH

Compatible with
AMPShare/Bosch
Professional
18 V batteries. |

Compatible avec les batteries 18 V
AMPShare/Bosch Professional. |

Compatible con baterías AMPShare/
Bosch Professional de 18 V.

